



The ultra-high speed direct thermal point-of-service printer with the most comprehensive features in its class

**OKIPOS® 407II: The fastest direct thermal POS printer on the market offers outstanding reliability, flexibility and functionality for high-volume applications.**

**OKI Printing Solutions offers a compact, reliable single-station POS printer that combines high performance with a low cost of operation.**

Designed to meet the growing need for smaller, faster POS printers, the OKIPOS 407II printer has a print speed of 250mm per second<sup>1</sup>—translating into 48 receipts per minute, at a crisp, clear 203 dpi resolution—for more transactions per hour in high-volume environments.

Built-in flexibility makes the OKIPOS 407II the ideal choice for a wide range of applications in retail point of sale, supermarkets, restaurants, hospitality, dry cleaners, health care, manufacturing, lottery, kiosks and banking.

**Engineered to keep you up and running** – The OKIPOS 407II has a streamlined, wall-mounted design that can free up valuable real estate at the sales counter. The printer has a long-life printhead and cutter for maximum uptime and fewer user interventions. An optional splash cover enhances dust and splash resistance in harsh environments. Its exceptional ease of use means the OKIPOS 407II can be up and running quickly with little need for staff training.

**Your choice for versatility** – The OKIPOS 407II prints on thermal paper and thermal labels, at widths up to 3.25" (82.5 mm) and thicknesses up to 0.15 mm. It holds a 3.9" (100 mm) roll of media.

In addition to superior media handling, the printer also offers a number of useful features— such as a “double resolution” mode to assure the best print quality of logos and graphics; 2-color capability; and 2-D barcode printing (PDF417 – QR code).

Standard configurations come with serial, parallel, USB or Ethernet ports. An optional ticket alarm is also available.

**Industry-leading support** – The OKIPOS 407II comes with a 2-year Advanced Overnight Exchange warranty.<sup>2</sup> Should you need technical assistance, you can speak to a live expert in North America 24/7/365 by calling, toll-free, **800-OKI-DATA** (800-654-3282).<sup>2</sup>

**The OKIPOS 407II: Ultra-fast and highly reliable POS print performance backed by the support you expect from OKI Printing Solutions.**

#### Highlights:

- Direct thermal POS printer
- Fastest print speed in its class: 250mm/sec – as fast as 48 receipts per minute<sup>1</sup>
- Extremely high reliability: printhead rated at 60 million lines; cutter at 2 million cuts<sup>3</sup>
- Handles thermal paper and thermal labels
- 203 dpi resolution
- Windows® Vista®, XP and 2000 compatibility
- Models available with serial, parallel, USB or Ethernet connectivity
- 24/7/365 live technical assistance<sup>2</sup>



<sup>1</sup> Published performance results based on laboratory testing. Individual results may vary.

<sup>2</sup> Available in the U.S. and Canada only.

<sup>3</sup> Depending on paper thickness.

# OKIPOS® 407II

Specifications		
Technology	Print Method	Direct thermal
	Print Speed	Up to 250 mm/sec <sup>1</sup> (48 RPM) <sup>1</sup>
	Printing Width	Max 3.15" (80 mm)
	Dot Density	203 dpi (8 dots/mm)
Interface	Standard	RS232 serial; IEEE 1284 bidirectional; USB; Ethernet
Compatibility	Operating Systems	Windows® Vista® (32 bit), XP (32 bit), 2000
	Emulation	Star Mode and ESC/POS
Font and Graphics	Character Matrix	9 x 24 dots, 12 x 24 dots
	Columns Capacity	48/64 or 53/71
	Character Set	95 Alphanumeric; International 32 (Star Mode)/37 (ESC/POS); 128 Graphic
	2D Bar Code	PDF417 – QR code
Paper Handling	Media Width	57.5mm (+/- 0.5), 79.5mm (+/- 0.5), 82.5mm (+/- 0.5)
	Media Roll Diameter	Max 3.9" (100 mm)
	Media Thickness	0.065mm – 0.150mm
	Cutter	Auto-cutter (standard, full or partial)
	Paper Loading	Drop-in
	Paper Sensor	Paper end (near-end sensor standard)
Environmental	Size (WxDxH)	5.78" x 8.38" x 5.79" (147 mm x 213 mm x 148 mm)
	Weight	3.85 lb. (1.75 kg)
	Electrical	DC 24 V +/-10%
	Operating Temperature	5° C – 45° C (10% 90% relative humidity)
	Storage	-20° C – 60° C (10% 90% relative humidity)
Reliability	Printhead	60 million lines (if paper thickness is between 60µm – 75µm)
	Cutter	2 million cuttings (if paper thickness is between 65µm – 100µm)
Warranty	Printer	2-Year Advanced Overnight Exchange <sup>3</sup>
Options	Accessories	External buzzer (ticket alarm)

Ordering Information	
Description	Part Number
OKIPOS 407II Parallel w/Cutter	62112603
OKIPOS 407II Serial w/Cutter	62112703
OKIPOS 407II USB w/Cutter	62112803
OKIPOS 407II Ethernet w/Cutter	62112903
OKIPOS 407II Parallel w/Cutter (Charcoal)	62113003
OKIPOS 407II Serial w/Cutter (Charcoal)	62113103
OKIPOS 407II USB w/Cutter (Charcoal)	62113203
OKIPOS 407II Ethernet w/Cutter (Charcoal)	62113303
<b>Options</b>	
External buzzer	72007002

<sup>1</sup> Published performance results based on laboratory testing. Individual results may vary.

<sup>2</sup> Depending on paper thickness.

<sup>3</sup> Available in the U.S. and Canada only.

Specifications are subject to change without notice.

© 2011 Oki Data Americas, Inc. OKI, OKIPOS Reg. T.M., Oki Electric Industry Co., Ltd. Windows, Vista Reg. T.M., Microsoft Corp. USB I/F logo T.M., Universal Serial Bus Implementers Forum, Inc.

For more information on Point of Service Printers from OKI Printing Solutions, contact your OKI representative. Or visit our Web site: [www.okiprintingsolutions.com](http://www.okiprintingsolutions.com)

**Please note:** OKI Printing Solution printers are designed to work best with genuine OKI® replacement consumables. Use of non-OKI consumables can result in less-than-adequate output, damage to the printer, and voiding of printer warranty.

For a complete list of OKI print media, please go to our Web site: [www.okiprintingsolutions.com](http://www.okiprintingsolutions.com)



## OKI DATA AMERICAS, INC.

**USA**  
2000 BISHOPS GATE BLVD.  
MOUNT LAUREL, NJ 08054-4620  
TEL: 800.OKI.DATA (800.654.3282)  
FAX: 856.222.5320

**CANADA**  
4140B SLADEVIEW CRESCENT  
UNITS 7 & 8  
MISSISSAUGA, ONTARIO L5L 6A1  
TEL: 905.608.5000  
FAX: 905.608.5040

**LATIN AMERICA**  
2000 BISHOPS GATE BLVD.  
MOUNT LAUREL, NJ 08054-4620  
TEL: 856.231.0002  
FAX: 856.222.5071

**OKI DATA DE MÉXICO, S.A. DE C.V.**  
MARIANO ESCOBEDO, 748 8º PISO  
COL. NUEVA ANZURES C.P. 11590  
MÉXICO, D.F.  
TEL: 55.5263.8780  
FAX: 55.5250.3501

**OKI DATA DO BRASIL INFORMÁTICA LTDA.**  
AV. ALFREDO EGÍDIO DE SOUZA ARANHA, 100  
BLOCO C – 4º ANDAR  
04726-170 – SÃO PAULO – SP – BRASIL  
TEL: 11.3444.3500  
FAX: 11.3444.3502

[WWW.OKIPRINTINGSOLUTIONS.COM](http://WWW.OKIPRINTINGSOLUTIONS.COM)