

Note Language: English**Version: 26 Validity: Valid Since 08.10.2010****Summary****Symptom**

The company OKI is member of the SAP Printer Vendor program and offers within this program connection software support for the printer model / device type pairs listed below.

For general information about the SAP Printer Vendor program please check note 1130927.

The printer model / device type combinations are visible in the newest data version of the "device type wizard". Please read note 1036961 for a description how to use the device type wizard and how to select one of the combinations shown below.

The device types (or ABAP PDL drivers or printer code pages) are delivered in the SAP standard in the releases/support packages listed below. If your system has the correct release, but not yet the appropriate support package level it is possible to install them in advance using the attachments to this note. Please download the files and proceed with the installation as described in note 1103422.

Certain features of the device types become active only with the following releases and support package levels:

Additional print options: (see note 1049778)

SAP_BASIS 6.20 SP63 and higher

SAP_BASIS 6.40 SP21 and higher

SAP_BASIS 7.00 SP14 and higher

SAP_BASIS 7.10 standard

Status feedback with SNMP:

SAP_BASIS 7.00 Enh1 and higher

SAP_BASIS 7.10 Enh1 and higher

Other terms

SPAD , device type , SAP Printer Vendor program

Reason and Prerequisites**Solution**

Supported Printer model/ device type combinations:

Number Printer Model Device type

001 OKI B440 OKI440

002 OKI B430 OKI440

003 OKI B420 OKI440

004 OKI B410 OKI440

005 ES4140 OKI440

006 OKI MB460 OKI440

007 OKI MB470 OKI440

008 OKI MB480 OKI440

009	ES4160 MFP	OKI440
010	ES4180 MFP	OKI440
011	OKI B6500	OKIB6500
012	OKI B6250	OKIB6500
013	ES6150	OKIB6500
014	OKI B930	OKIB930
015	ES9130	OKIB930
016	OKI MC860	OKIA3NF1
017	ES8460 MFP	OKIA3NF1
018	OKI C830	OKIA3NF1
019	ES8430	OKIA3NF1
020	CX2633 MFP	OKIA3NF1
021	OKI C5950	OKIA3NF1
022	OKI C5750	OKIA3NF1
023	OKI C6150	OKIA3NF1
024	ES2632a4	OKIA3NF1
025	OKI MC560	OKIA3NF1
026	ES5460 MFP	OKIA3NF1
027	CX2033 MFP	OKIA3NF1
028	OKI C9850	OKIA3WF1
029	OKI C9850 MFP	OKIA3WF1
030	ES3640 Pro	OKIA3WF1
031	ES3640 Pro MFP	OKIA3WF1
032	CX3641 MFP	OKIA3WF1
033	OKI MC860	OKIA3TR1
034	ES8460 MFP	OKIA3TR1
035	OKI C830	OKIA3TR1
036	ES8430	OKIA3TR1
037	CX2633 MFP	OKIA3TR1
038	OKI C5950	OKIA3TR1
039	OKI C5750	OKIA3TR1
040	OKI C6150	OKIA3TR1
041	ES2632a4	OKIA3TR1
042	OKI MC560	OKIA3TR1
043	ES5460 MFP	OKIA3TR1
044	CX2033 MFP	OKIA3TR1
045	OKI C711	OKIA4JP1
046	OKI C610	OKIA4JP1
047	OKI C530	OKIA4JP1
048	OKI C830	OKIA4JP1
049	OKI B431	OKBCJP01
050	OKI B411	OKBCJP01
051	OKI B840	OKBCJP02
052	OKI B820	OKBCJP02
053	OKI MC361	OKCCJP01
054	OKI MC561	OKCCJP02
055	OKI C710	OKIA3NF1
056	OKI B710	OKIB700
057	OKI B720	OKIB700
058	OKI B730	OKIB700
059	ES7120	OKIB700
060	ES7130	OKIB700
061	OKI MPS730b	OKIB700
062	OKI C610	OKA3UTF8
063	OKI C711	OKA3UTF8
064	ES6410	OKA3UTF8
065	ES7411	OKA3UTF8
066	OKI MB780	OKMB780

067 OKI MB790f OKMB790
068 OKI MB790m OKMB790

Details:

001 OKI B440/OKI440 (Version 1)
002 OKI B430/OKI440 (Version 1)
003 OKI B420/OKI440 (Version 1)
004 OKI B410/OKI440 (Version 1)
005 ES4140/OKI440 (Version 1)
006 OKI MB460/OKI440 (Version 1)
007 OKI MB470/OKI440 (Version 1)
008 OKI MB480/OKI440 (Version 1)
009 ES4160 MFP/OKI440 (Version 1)
010 ES4180 MFP/OKI440 (Version 1)

Properties:

- Supported languages: Latin1
- PDL: PCL
- Paper sizes: A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Monochrome LED Printer
- Additional print options:
 - Input trays
 - Double-sided Printing
- Barcode Printing
 - ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
 - BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
 - All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

Details:

011 OKI B6500/OKIB6500 (Version 1)
012 OKI B6250/OKIB6500 (Version 1)
013 ES6150/OKIB6500 (Version 1)

Properties:

- Supported languages: Latin1
- PDL: PCL
- Paper sizes: A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Monochrome LED Printer
- Additional print options:
 - Input trays
 - Output trays
 - Double-sided Printing
- Barcode Printing
 - ARTNR, AUFNR, BARCLVS, BC_93, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
 - BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported

014 B930/OKIB930 (Version 1)
015 ES9130/OKIBB930 (Version 1)

Properties:

- Supported languages: Latin1
- PDL: PCL
- Paper sizes: A3,A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Monochrome LED Printer
- Additional print options:
 - Input trays
 - Output trays
 - Double-sided Printing
 - Stapling
 - Punching
 - Job Separation
- Barcode Printing
 - ARTNR, AUFNR, BARCLVS, BC_93, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
 - BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported

016 OKI MC860/OKIA3NF1 (Version 1)
017 ES8460 MFP/OKIA3NF1 (Version 1)
018 OKI C830/OKIA3NF1 (Version 1)
019 ES8430/OKIA3NF1 (Version 1)
020 CX2633 MFP/OKIA3NF1 (Version 1)

- Supported languages: Latin1
- PDL: PCL
- Paper sizes: A3,A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Color LED Printer
- Additional print options:
 - Input trays
 - Double-sided Printing
 - Print in color
 - Password protection
- Barcode Printing
 - ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
 - BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
 - All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

021 OKI C5950/OKIA3NF1 (Version 1)
022 OKI C5750/OKIA3NF1 (Version 1)
023 OKI C6150/OKIA3NF1 (Version 1)
024 ES2632a4/OKIA3NF1 (Version 1)

- Supported languages: Latin1
- PDL: PCL
- Paper sizes: A4,A5, LETTER, EXECUTIVE, LEGAL

- Printer Type: Color LED Printer
- Additional print options:
 - Input trays
 - Double-sided Printing
 - Print in color
 - Password protection
- Barcode Printing
 - ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
 - BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
 - All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

025 OKI MC560/OKIA3NF1 (Version 1)

026 ES5460 MFP/OKIA3NF1 (Version 1)

027 CX2033 MFP/OKIA3NF1 (Version 1)

- Supported languages: Latin1
- PDL: PCL
- Paper sizes: A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Color LED Printer
- Additional print options:
 - Input trays
 - Double-sided Printing
 - Print in color
 - Password protection
- Barcode Printing
 - ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
 - BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
 - Note that SNMP status feedback does not work correctly with these devices so should not be used.

028 OKI C9850/OKIA3WF1

029 OKI C9850 MFP/OKIA3WF1

030 ES3640 Pro/OKIA3WF1

031 ES3640 Pro MFP/OKIA3WF1

032 CX3641 MFP/OKIA3WF1

- Supported languages: Latin1
- PDL: PCL
- Paper sizes: A3, A4, A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Color LED Printer
- Additional print options:
 - Input trays
 - Double-sided Printing
 - Print in color
 - Stapling
 - Punching
- Barcode Printing

-ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported, but require additional hardware.

- BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
 - Note that SNMP status feedback does not work correctly with these devices so should not be used.

033 OKI MC860/OKIA3TR1 (Version 1)

034 ES8460 MFP/OKIA3TR1 (Version 1)

035 OKI C830/OKIA3TR1 (Version 1)

036 ES8430/OKIA3TR1 (Version 1)

037 CX2633 MFP/OKIA3TR1 (Version 1)

- Supported languages: ISO9 (Turkey)
- PDL: PCL
- Paper sizes: A3,A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Color LED Printer
- Additional print options:
 - Input trays
 - Double-sided Printing
 - Print in color
 - Password protection
- Barcode Printing

-ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.

- BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
 - All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

038 OKI C5950/OKIA3TR1 (Version 1)

039 OKI C5750/OKIA3TR1 (Version 1)

040 OKI C6150/OKIA3TR1 (Version 1)

041 ES2632a4/OKIA3TR1 (Version 1)

- Supported languages: ISO9 (Turkey)
- PDL: PCL
- Paper sizes: A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Color LED Printer
- Additional print options:
 - Input trays
 - Double-sided Printing
 - Print in color
 - Password protection
- Barcode Printing

-ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.

- BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback

- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

042 OKI MC560/OKIA3TR1 (Version 1)

043 ES5460 MFP/OKIA3TR1 (Version 1)

044 CX2033 MFP/OKIA3TR1 (Version 1)

- Supported languages: ISO9 (Turkey)

- PDL: PCL

- Paper sizes: A4,A5, LETTER, EXECUTIVE, LEGAL

- Printer Type: Color LED Printer

- Additional print options:

- Input trays

- Double-sided Printing

- Print in color

- Password protection

- Barcode Printing

-ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.

-BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported

- SNMP status feedback

- Note that SNMP status feedback does not work correctly with these devices so should not be used.

045 OKI C711/OKIA4JP1 (Version 1)

046 OKI C610/OKIA4JP1 (Version 1)

047 OKI C530/OKIA4JP1 (Version 1)

048 OKI C830/OKIA4JP1 (Version 1)

- Supported languages: Japanese (SJIS)

- PDL: PCL

- Paper sizes: A3,A4,A5, LETTER, EXECUTIVE, LEGAL, JPHAGAKI

- Printer Type: Color LED Printer

- Additional print options:

- Input trays

- Double-sided Printing

- Print in color

- Password protection

- Barcode Printing

-ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.

-BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported

- SNMP status feedback

- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

049 OKI B431/OKBCJP01 (Version 1)

050 OKI B411/OKBCJP01 (Version 1)

- Supported languages: Japanese (SJIS)

- PDL: PCL

- Paper sizes: A4,A5, LETTER, EXECUTIVE, LEGAL, JPHAGAKI
- Printer Type: Monochrome LED Printer
- Additional print options:
 - Input trays
 - Double-sided Printing
- Barcode Printing
 - ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
 - BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
 - All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

051 OKI B840/OKBCJP02 (Version 1)

052 OKI B820/OKBCJP02 (Version 1)

- Supported languages: Japanese (SJIS)
- PDL: PCL
- Paper sizes: A3,A4,A5, LETTER, EXECUTIVE, LEGAL, JPHAGAKI
- Printer Type: Monochrome LED Printer
- Additional print options:
 - Input trays
 - Double-sided Printing
 - Password protection
- Barcode Printing
 - ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
 - BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
 - All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

053 OKI MC361/OKCCJP01 (Version 1)

- Supported languages: Japanese (SJIS)
- PDL: PCL
- Paper sizes: A4,A5, LETTER, EXECUTIVE, LEGAL, JPHAGAKI
- Printer Type: Color LED Printer
- Additional print options:
 - Input trays
 - Double-sided Printing
 - Print in color
- Barcode Printing
 - ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
 - BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback

- All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

054 OKI MC561/OKCCJP02 (Version 1)

- Supported languages: Japanese (SJIS)
- PDL: PCL
- Paper sizes: A4,A5, LETTER, EXECUTIVE, LEGAL, JPHAGAKI
- Printer Type: Color LED Printer
- Additional print options:
 - Input trays
 - Double-sided Printing
 - Print in color
 - Password protection
- Barcode Printing
 - ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
 - BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
 - All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

055 OKI C710/OKIA3NF1 (Version 1)

- Supported languages: Latin1
- PDL: PCL
- Paper sizes: A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Color LED Printer
- Additional print options:
 - Input trays
 - Double-sided Printing
 - Print in color
 - Password protection
- Barcode Printing
 - ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
 - BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
 - All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.

Details:

- 056 OKI B710/OKIB700 (Version 2)
- 057 OKI B720/OKIB700 (Version 2)
- 058 OKI B730/OKIB700 (Version 2)
- 059 ES7120/OKIB700 (Version 2)
- 060 ES7130/OKIB700 (Version 2)
- 061 OKI MPS730b/OKIB700 (Version 2)

Properties:

- Supported languages: Latin1
- PDL: PCL
- Paper sizes: A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Monochrome LED Printer
- Additional print options:
 - Input trays
 - Output trays
 - Double-sided Printing
- Barcode Printing
 - ARTNR, AUFNR, BARCLVS, BC_93, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
 - BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported

062 OKI C610 /OKA3UTF8 (Version 00117)

063 OKI C711 /OKA3UTF8 (Version 00117)

064 ES6410/OKA3UTF8 (Version 00117)

065 ES7411/OKA3UTF8 (Version 00117)

- Supported languages:
Latin1, Latin2 (ISO2), Cyrillic (ISO5), Greek (ISO7), Turkey (ISO9)
- PDL: PCL
- Paper sizes: A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Color LED Printer
- Additional print options:
 - Input trays
 - Double-sided Printing
 - Print in color
 - Password protection
- Barcode Printing
 - ARTNR, AUFNR, BARCLVS, BC_C128B, BC_CD39, BC_CD39C, BC_EAN8, BC_EAN13, BC_EANH, BC_I25, BC_I25C, BC_PSN5, BC_PSN9, BC_PSN11, C128A_00, C128A_01, C128B_00, C128B_01, CD39C_00, CD39C_01, CD39__00, CD39__01, KUNAUNR, KUNAUPS, MBBARC, MBBARC1, RSNUM, RSPOS and RUECKNR are supported without additional hardware.
 - BC_93, BC_MSI, BC_MSIC, MC_MSIC1 and MC_MSIC2 are NOT supported
- SNMP status feedback
 - All models with network connection are supported. Status feedback is limited to Pending, Processing, Completed or Unknown. No additional information is displayed regarding conditions requiring user intervention on the device, e.g. Paper Out or manual feed request.
- Printer firmware CU3.02 or above is required.

066 OKI MB780 /OKMB780

067 OKI MB790f /OKMB790

068 OKI MB790m /OKMB790

Properties:

- Supported languages: Latin1
- PDL: PCL5
- Paper sizes: A4,A5, LETTER, EXECUTIVE, LEGAL
- Printer Type: Monochrome laser printer
- Additional print options:
 - Input trays
 - Output tray selection
 - Double-sided Printing

- Password protection
 - Vendor-defined (2-up printing)
-

Header Data

SAP Note No.: 1258625
Note Language: English
Master Language: English
Version: 26
Valid Since: 08.10.2010

Release Status: Released for Customer
Released on: 08.10.2010 13:44:04
Released by: Christian Hansen

Priority: Recommendations/additional info

Author: Nobuyuki Yokoyama
Entered by: Christian Hansen
Processed by: Christian Hansen
Last Changed by: Christian Hansen
On: 08.10.2010 13:44:05

Category: Special development
Standard Note: No

Primary Component: BC-CCM-PRN-PVP-OK SAP Printer Vendor program:
Oki

The Note is release-independent

Related Notes

Number	Short Text
1097990	List of Printer Vendor Wizard Notes

Attachments



File Type	File Name	Language	Size
ZIP	OKI_DevTyps.zip	E	774 KB